SPECIFIC	CATIONS SHEET	•			- D ~	
Series	□ D-325			_	J D C	
	☐ E-325			LOADING D	OCK COMPANY (	LDC) INC.
Customer:		Da	ate:		P.O. #:	
Salesman:		Da	ate Red	quired:		
Door Opening:	"w x	"h Er	nd Use	:		
Dock Height:	nh Bumper Projection:	Ta	.g:		# of Unit	s:
Approach:	☐ Incline ☐ Decline ☐	Sh	nip Via:			<u>-</u>
Header Airbag Fabric: _	Colour				•	☐ 3rd Party
Side Pad Fabric:	Colour	Sh	nip to:			
Flap Fabric:	Colour					
Storage Curtain Fabric:_	Colour					
∕ellow Guide	/   Motol Dov	On/Off Pilot Light		Metal Face Plate	☐ Wiring Diagram	
FRONT VIE	Unit Width Std. 116"	<b>&gt;</b>			Head Frame Projec Greater Than Side Ba	ction is 12" ag Projection
			<u> </u>			
Unit Height Off Grade Std. 188"	(LDC)	I I O		Head Bag Drop Std. 50"  Unit Height Std. 140"  ght  k Height td. 48"		Rectangular Side Pads  ertical Height Std. 124"  Bevelled Side Pads
Options:		☐ 2 VERTIC ☐ 1 GALVAI ☐ 1½ HP. I ☐ 2 GALVA	RAME C/ CAL FOAI NIZED TE MOTOR ( NIZED S	N AIR BAG, SPRING & M PADS C/W GUIDE ST RIM ANGLE C/W SIDE BRACKET & DE SUPPORTS (1 LEF CURTAIN C/W YELLOW	RETENTION CORDS [ TRIPS [ VELCRO [ T & 1 RIGHT)	Hardware List  4 %" x 3" Sleeve Anchors  6 FLAT BRACKETS  6 ANGLE BRACKETS  20 %" x 1%" Sleeve Anchors  50 #14 x 1½" Wood Screws  15 ROOFING NAILS  1 INSTALLATION INSTRUCTION
Cut by:	•		- -	Approved for m	anufacturing by:	
Assembled by:	Shipped by:		-			
Inspected by:	# of Pieces			Date:		